

Accessories for Commercial Fans

Power Roof Ventilation

5ACC..FS, 5ACC..FT



Fixed Non-Ventilated Curb

Manufactured from heavy gauge galvanized steel. Corners are welded construction. The curb features fiberglass insulation that deadens sound and minimizes heat loss. The curb is equipped with shutter flanges and a 1 1/2" and a wood nailer (fixed roof curbs only).

Specification Data

Model 8" / 12"	Fan Size	5FSU Size	Shipping weight, lbs	Shipping class	Item #	MSRP, USD
5ACC15FS	REC 54/6	-	11	2	49580	113.-
5ACC19FS	REC 8..10	-	28	2	471062	143.-
5ACC17FS / 5ACC17FT	8.5, 10	-	24 / 29	2	47206 / 47207	127.- / 162.-
5ACC20FS / 5ACC20FT	12, 13	-	28 / 33	2	47212 / 47213	140.- / 174.-
5ACC24FS / 5ACC24FT	15, 16	-	33 / 38	2	47217 / 47941	151.- / 189.-
5ACC28FS / 5ACC28FT	18, 20	5FSU 10	40 / 47	2	47221 / 47222	169.- / 210.-
5ACC32FS / 5ACC32FT	24	5FSU 12, 15	46 / 53	2	47226 / 47227	188.- / 232.-
5ACC40FS / 5ACC40FT	30	5FSU 18	57 / 68	2	47233 / 47901	237.- / 360.-
5ACC44FS / 5ACC44FT	36		63 / 74	2	47237 / 47238	273.- / 346.-



5ACC..VC



Fixed Ventilated Curb

Manufactured from galvanized steel. The curb features stamped louvers on curb sides that provide ventilation to hot exhaust ducts to protect building and roof members. Self-flashing design incorporates flat mounting flange for fastening directly to the roof deck. Curb is suitable for UL 762 commercial kitchen exhaust applications.

Specification Data

Model	Fan Size	Curb Height, inch	Shipping weight, lbs	Shipping class	Item #	MSRP, USD
5ACC 17VC	8.5, 10	24	38	2	47208	215.-
5ACC 20VC	12, 13	24	38	2	47214	230.-
5ACC 24VC	15, 16	24	47	2	47219	245.-
5ACC 28VC	18, 20	24	54	2	47223	269.-
5ACC 32VC	24	24	52	2	47228	329.-
5ACC 40VC	30	18	63	2	47234	403.-
5ACC 44VC	36	18	92	2	47665	426.-



Accessories for Commercial Fans

Power Roof Ventilation

5ACC..RD



Roof Mount Damper

Manufactured from 19-gauge galvanized steel frame 2" deep with 1" flange. For quiet operation aluminum blades have felted edges. Pre-punched conduit hole knock-out.

Specification Data

Model	Fan Size	Recommended Roof Opening	Outside Flange, inch	Shipping weight, lbs	Shipping class	Item #	MSRP, USD
5ACC 12RD	8.5, 10	12 1/2 x 12 1/2	14 x 14	3	1	47196	33.-
5ACC 15RD	12, 13	15 1/2 x 15 1/2	17 x 17	4	1	47203	39.-
5ACC 19RD	15, 16	19 1/2 x 19 1/2	21 x 21	5	1	47210	45.-
5ACC 23RD	18, 20	23 1/2 x 23 1/2	25 x 25	9	1	47215	58.-
5ACC 27RD	24	27 1/2 x 27 1/2	29 x 29	11	1	47220	67.-
5ACC 35RD	30	35 1/2 x 35 1/2	37 x 37	16	1	47229	95.-
5ACC 39RD	36	39 1/2 x 39 1/2	41 x 41	21	1	47232	115.-



5ACC..SD



Supply Damper

Manufactured from 19-gauge galvanized steel, frame is 2" deep with 1" flange. Aluminum blades have felted edges for quiet operation. System fan forces blades to open; integral spring returns blades to closed position. Pre-punched conduit hole knockout. Can be mounted on shelf in roof curb models 5ACC..FS / FT for supply air to building. Use with model series 5FSU filtered supply units. Shipping class 2.

Specification Data

Model	5FSU Size	Recommended Roof Opening	Fits curb model	Outside Flange, inch	Shipping weight, lbs	Item #	MSRP, USD
5ACC 23SD	5FSU 10	23 1/2 x 23 1/2	5ACC28FS / FT	25 x 25	9	482839	73.-
5ACC 27SD	5FSU 12, 15	27 1/2 x 27 1/2	5ACC32FS / FT	29 x 29	11	482840	85.-
5ACC 35SD	5FSU 18	35 1/2 x 35 1/2	5ACC40FS / FT	37 x 37	17	482842	118.-



SPEED CONTROLS AND DISCONNECT SWITCHES

Find appropriate speed control and disconnect switch accessories in the **Switches and Controls for Ventilation** section of accessories. See page 259.

Accessories for Commercial Fans


Power Roof Ventilation

5ACC..HK



Hinge Kit

Model 5ACC 00HK suitable for 10" - 20" and model 5ACC 01HK suitable for 24" - 36". Allows entire fan to swing away for access to the wheel and ductwork.



Specification Data

Model	Fan Size	Shipping weight, lbs	Shipping class	Item #	MSRP, USD
5ACC 00HK	10 - 20	4	1	47179	97.-
5ACC 01HK	24 - 36	40	1	47181	330.-

5ACC..GC



Grease Collector

The grease collector box manufactured from heavy gauge galvanized steel. It fastens to a ventilator base. Easy to remove for cleaning. Diverts and traps heavy residual grease while protecting roof surface. Available in 2 sizes.



Specification Data

Model	Fan Size	Length, inch	Width, inch	Shipping weight, lbs	Shipping class	Item #	MSRP, USD
5ACC 00GC	8' / 12"	14	5	4	1	47178	111.-
5ACC 01GC	15 - 36	24	7	12	1	47180	143.-

Side Wall Ventilation

2DVP



Venturi Frame

For customers assembling their own wall fans, this venturi frame is just the ticket! Made in the USA out of pressed galvanized steel, this heavy duty Venturi features a welded motor bracket and black powder coating. Just add your fan blade and motor.



Specification Data

Model	Fan Size	Shipping weight, lbs	Shipping class	Item #	MSRP, USD
2DVP 12	12	24	1	47420	81.-
2DVP 16	16	24	1	47755	103.-
2DVP 24	24	24	2	47725	124.-
2DVP 30	30	24	2	47614	162.-

1ACC..WH



Weatherhood

Shield fan and damper opening in walls from rain and snow. For direct- and belt-drive propeller fans. Sized to easily mount to wall collar. Galvanized steel construction. A bird screen is included. Weatherhoods are shipped unassembled with assembly hardware included. Shipping class 2.



Specification Data

Model	Fan Size	Recommended Wall Opening	Outside Flange, inch	Weight, lbs	Shipping class	Item #	MSRP, USD
1ACC24WH	24	28 1/4	32 x 32	31	2	47015	188.-
1ACC30WH	30	34 1/4	38 x 38	44	2	47020	256.-
1ACC36WH	36	40 1/4	44 x 44	58	2	47025	315.-
1ACC42WH	42	46 1/4	50 x 50	74	2	47030	323.-
1ACC48WH	48	54 1/4	58 x 58	97	2	47035	490.-

Accessories for Commercial Fans

Side Wall Ventilation

1ACC..WD



Wall Damper

Single panel exhaust shutter manufactured from 19-gauge galvanized steel frame 3" deep with 1 5/8" flange. For quiet operation aluminum blades have felted edges. The damper is designed for use with 2VLD ventilator models. Models 42WD and 48WD have double panel.



Specification Data

Model	Fan Size	Recommended Wall Opening	Outside Flange, inch	Weight, lbs	Shipping class	Item #	MSRP, USD
1ACC12WD	12	13 x 13	15 x 15	5	1	47004	60.-
1ACC16WD	16	17 x 17	19 x 19	6	1	47006	63.-
1ACC18WD	18	19 x 19	21 x 21	6	1	47008	63.-
1ACC20WD	20	21 x 21	23 x 23	7	2	47010	68.-
1ACC24WD	24	25 x 25	27 x 27	9	2	47014	84.-
1ACC30WD	30	31 x 31	33 x 33	17	2	47019	90.-
1ACC36WD	36	37 x 37	39 x 39	22	2	47024	96.-
1ACC42WD	42	43 x 43	45 x 45	26	2	47029	113.-
1ACC48WD	48	49 x 49	51 x 51	31	2	47034	209.-

1ACC..MD



Motorized Damper

Manufactured from 14-gauge galvanized steel frame 2" deep with 1" flange. Damper is equipped with a motor to open and a spring return to close. Maximum airflow is 3500 FPM. 120/240V, 0.19/0.11A, 60 Hz. 54MD and 60MD models are 240V only.



Specification Data

Model	Fan Size	Recommended Wall Opening	Outside Flange, inch	Weight, lbs	Shipping class	Item #	MSRP, USD
1ACC24MD	24	25 x 25	27 x 27	29	2	47011	290.-
1ACC30MD	30	31 x 31	33 x 33	39	2	47016	478.-
1ACC36MD	36	37 x 37	39 x 39	51	2	47021	545.-
1ACC42MD	42	43 x 43	45 x 45	67	2	47026	628.-
1ACC48MD	48	49 x 49	51 x 51	83	2	47031	693.-
1ACC54MD	54	55 x 55	57 x 57	114	2	47442	1,036.-
1ACC60MD	60	61 x 61	63 x 63	130	2	47980	1,106.-

1ACC..SG



Intake Guards

Manufactured from 20-gauge galvanized steel frame (except 48SG - 18-gauge). Screens are hinged and removeable for easy access. These guards comply with OSHA regulations. Shipped knocked down with assembly hardware included.



Specification Data

Model	Fan Size	Shipping weight, lbs	Shipping class	Item #	MSRP, USD
1ACC12SG	12	35	1	47003	117.-
1ACC16SG	16	39	1	47005	155.-
1ACC24SG	24	35	1	47012	156.-
1ACC30SG	30	39	1	47017	207.-
1ACC36SG	36	61	2	47022	347.-
1ACC42SG	42	61	2	47027	401.-
1ACC48SG	48	120	2	47032	512.-

1ACC..WC



Wall Collar

An easy way to install vertically mounted supply and exhaust fans. An internal flange is provided for shutter mounting. The external flange provides a flashing for the wall opening. Galvanized steel construction.



Specification Data

Model	Fan Size	Shipping weight, lbs	Shipping class	Item #	MSRP, USD
1ACC24WC	24	53	2	47013	178.-
1ACC30WC	30	77	2	47018	255.-
1ACC36WC	36	88	2	47023	308.-
1ACC42WC	42	97	2	47028	314.-
1ACC48WC	48	123	2	47033	396.-