



# IN-LINE BOOSTER FAN

**BOOST AIRFLOW TO ROOMS THAT ARE TOO HOT OR TOO COLD**

## SINGLE SPEED CORDED FANS

- Solves air delivery problems without major system rework or expense
- Can be installed at any angle
- Engineered for maximum boost and quiet operation
- Easy installation for metal or flex duct
- Saves on utility bills year round
- 9 MODELS AVAILABLE

Engineered for maximum boost and quiet operation. Motor 110V, Class B, Thermally Protected.



Model	Diameter	Blade	Max Boosted CFM	Free Air CFM	Watts	Amps
DB100C	6" - 8"	Polycarbonate	250	160	30	0.35
★DB200C	6"	Polycarbonate	250	160	30	0.35
★DB204C	4"	Polycarbonate	80	65	30	0.30
DB205C	5"	Polycarbonate	130	75	30	0.35
DB206C	6"	Polycarbonate	250	160	30	0.35
DB208C	8"	Polycarbonate	500	210	55	0.70
DB6GTC	6"	Aluminum	350	180	55	0.70
DB210C	10"	Aluminum	650	300	120	1.50
DB212C	12"	Aluminum	800	650	120	1.50




For automatic operation, see the optional DuctStat<sup>®</sup>, Plug-In Thermostat<sup>™</sup>.

\*Both ends crimped.

**NEVER USE A RHEOSTAT TO CONTROL FAN SPEED.**

SUNCOURT INC.  
Durant, IA 52747-0040  
1.800.999.FANS

[WWW.SUNCOURT.COM](http://WWW.SUNCOURT.COM)



Assembled  
in USA

CATDBC-0621



# IN-LINE BOOSTER FAN

BOOST AIRFLOW TO ROOMS THAT ARE TOO HOT OR TOO COLD

## 2-SPEED FANS

- Solves air delivery problems without major system rework or expense
- Can be installed at any angle
- Engineered for maximum boost and quiet operation
- Easy installation for metal or flex duct
- Saves on utility bills year round
- 3 MODELS AVAILABLE

Engineered for maximum boost and quiet operation.  
Motor 110V, Class B, Thermally Protected.



Model	Diameter	Blade	Max Boosted CFM	Free Air CFM	Watts	Amps
DB306E	6"	Polycarbonate	300	160/180	30	0.35
DB308E	8"	Polycarbonate	600	210/250	60	0.85
DB310E	10"	Aluminum	900	300/460	135	1.70



For automatic operation, see the optional DuctStat®, Plug-In Thermostat™.

2-Speed, can be wired for high or low.

The in-line duct fans can be speed controlled using the Suncourt VS100 solid state speed control.

Follow the installation instructions included with the VS100.

**NEVER USE A RHEOSTAT TO CONTROL FAN SPEED.**

SUNCOURT INC.  
Durant, IA 52747-0040  
1.800.999.FANS

[WWW.SUNCOURT.COM](http://WWW.SUNCOURT.COM)



Assembled  
in USA

CATDB2E-0621



# IN-LINE BOOSTER FAN

BOOST AIRFLOW TO ROOMS THAT ARE TOO HOT OR TOO COLD

## 4-POLE FANS

- Solves air delivery problems without major system rework or expense
- Can be installed at any angle
- Engineered for maximum boost and quiet operation
- Easy installation for metal or flex duct
- Saves on utility bills year round
- 3 MODELS AVAILABLE

Engineered for maximum boost and quiet operation.  
Motor 110V, Class B, Thermally Protected.




Model	Diameter	Blade	Max Boosted CFM	Free Air CFM	Watts	Amps
DB412E	12"	Aluminum	1160	700	180	1.57
DB414E	14"	Aluminum	1580	900	180	1.57
DB416E	16"	Aluminum	1760	1100	180	1.57



For automatic operation, see the optional DuctStat<sup>®</sup>, Plug-In Thermostat<sup>™</sup>.  
The in-line duct fans can be speed controlled using the Suncourt VS100 solid state speed control.  
Follow the installation instructions included with the VS100.  
**NEVER USE A RHEOSTAT TO CONTROL FAN SPEED.**

**SUNCOURT INC.**  
Durant, IA 52747-0040  
1.800.999.FANS

**WWW.SUNCOURT.COM**



**Assembled  
in USA**

CATDB4E-0621