### SS3-200

## ACT D'MAND Kontrols® Systems



SUBMITTAL DATA	
JOB/CUSTOMER:	SUBMITTED BY:
ENGINEER:	APPROVED BY:
CONTRACTOR:	ORDER NO:
SPECIFICATION REFERENCE:	





#### **OPTIONAL ACCESSORIES**

- ☐ Hardwired LED Button
- ☐ Hardwired Rocker Switch
- ☐ Hardwired Motion Sensor
- ☐ Bluetooth Wireless Transmitter Kit
- ☐ Bluetooth Wireless Motion Sensor
  - 5011501
- ☐ Bluetooth Repeater
- ☐ Under Sink Mounting Kit (For Systems w/o Return Lines)

#### **INCLUDES**

The Original D'MAND KONTROLS® System Standard package comes with:


- (1) 3-Speed Control Box with Power Cord, Activation Wires
- (1) SS3-200 Pump


- (1) Integrated Check Valve
- (1) Integrated Temperature Sensor
- (1) Hardwired Activation Button

(2) Flanges with Bolts and Nuts

TECHNICAL DATA	
FLOW RANGE: 0-33 GPM	MAX. WORKING PRESSURE: 145 PSI
HEAD RANGE: 0-29 Ft.	CONNECTORS: GF 15/26 Flange (With ¾" Stainless Steel MIP not shown in picture)
MOTORS: 2-POLE SINGLE PHASE	RPM/HP: 3450/.262hp
MIN. FLUID TEMPERATURE: 36°F	VOLTAGE (max. spd.): 115V/197 watts/1.80 Amps
MAX. FLUID TEMPERATURE: 230°F	APPROX SHIP WEIGHT: 15 LBS

#### **DIMENSIONS**





# H H H UPS26-99FC/BFC 60 Hz

**PERFORMANCE CHART** 

PHONE: (800) 200-1956 www.GotHotWater.com FAX: (714) 668-1927