



## Key Features

- Designed for small to medium-scale wine cellars
- Unit power connections available from side or rear
- Centrifugal fans deliver efficient, quiet cooling
- Single-piece mounting bracket
- 30°F temperature differential (55°F cellar with  $\leq 85^\circ\text{F}$  intake)
- Digital controller conveniently located on the face of the unit
- Liquid-temperature-measuring bottle probe for precision control
- Condensate management system evaporates up to 3 oz. per hour

## Specifications

Model	2200	3300	4400	8800
Cellar Size (cu. ft.)	300*	650*	1000*	1500*
BTU/h (w/85°F condenser air intake temperature)	1453	2049	2253	4241
Dimensions	17.5"L x 14.25"W x 15.75"H			21.64"L x 14.25"W x 22.56"H
Refrigerant	R-134a			
HP	1/8	1/6	1/6+	1/2
Voltage Rating	115V (20 amp dedicated circuit required); 230V (subject to availability)			
Weight (lb.)	65			104
Amps	3.2 (running amps)	3.7 (running amps)	4.7 (running amps)	10.9 (running amps)
Drain Line	½" Condensate (rear location only)			
Installation	Through-the-wall, partially ducted			
Thermostat	Advanced digital display, liquid-temperature-measuring bottle probe (retractable cable)			
Temp. Delta	Can maintain a 55°F cellar temperature with up to 85°F condenser air intake temperature			
Ducting Options	Exhaust air can be ducted using the optional ducting kit			
Warranty	2-year limited warranty & up to an additional (6) month grace period for install / 5-year limited warranty (compressor)			

\*Approximated in an environment that is fully insulated and sealed with a proper vapor barrier. Each wine cellar is unique and has specific cooling requirements. Heat load calculations should always be performed prior to selecting a cooling unit.

## Optional Accessories

- Exhaust ducting kit
- Exterior housing
- UV-C Lighting System